

5061.673
17 SEP 2004(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/086527 A1(51) International Patent Classification⁷: A61M 39/04

(21) International Application Number: PCT/SE03/00527

(22) International Filing Date: 2 April 2003 (02.04.2003)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0201054-4 8 April 2002 (08.04.2002) SE(71) Applicant (for all designated States except US): TRAN-
SCUTAN AB [SE/SE]; Björnflokevägen 35, S-162 45
Vällingby (SE).

(72) Inventors; and


(75) Inventors/Applicants (for US only): LUNDGREN, Dan
[SE/SE]; Askims Kyrkväg 5, S-436 51 Hovås (SE). NY-
MAN, Rickard [SE/SE]; Svartbäcksgatan 41, S-753 32
Uppsala (SE).(74) Agents: SUNDSTRÖM, Per et al.; Stenhagen Patentbyrå
AB, P.O. Box 4630, S-116 91 Stockholm (SE).(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AE,
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES,
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,

[Continued on next page]

(54) Title: A TRANSCUTANEOUS PORTAL DEVICE



(57) Abstract: A transcutaneous portal arrangement comprises a portal body (1) that includes a bottom wall (7) which has a through-passing opening or transit (8) for accommodating a catheter (9), a tubular element (10) that includes an end-portion (11) which is inserted into the end-portion (11) of the catheter (9), and clamping means (5, 38, 61, 62) for clamping the end-portion of the tubular element (10) against said bottom wall around said through-passing opening, such as to sealingly clamp the outer and the inner wall of the catheter around the edge of the opening (8) and around the periphery of the tubular element respectively.

WO 03/086527 A1



MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL,

PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A TRANSCUTANEOUS PORTAL DEVICE

The present invention relates to a transcutaneous portal device of the kind defined in the preamble of Claim 1.

5

WO-89/06897 teaches a transcutaneous portal device that includes a sealing coupling or union for releasably connecting in the portal one end part of an outer conduit and one end part of a catheter. The catheter extends into the body interior.

10

The portal itself, which is also described in PCT SE-87/00201 for instance, is suitably comprised of titanium and has generally the form of a cup whose wall carries on its outside a ring flange that preferably includes slots and openings that facilitate stable tissue ingrowth. The upper edge portion of the cup carries a thread, which co-acts with a corresponding thread on a cap or lid. An elastic sealing plug can be inserted into the cup so as to essentially fill-out the same. The body can be compressed axially with the aid of the cap thread joint, wherewith the body swells radially and seals against and around the inner wall of the cup, therewith effectively closing the central channel in the plug. An outer conduit can be forced through the plug channel and therewith placed in communication with the bottom space of the cup beneath the plug.

20

A catheter extends through an opening in the bottom wall of the cup/portal. Resting on the inner side of the bottom wall is a plate that includes an opening for the end portion of the catheter. This catheter end portion includes a head, which prevents the catheter from being drawn out through the plate opening.

25

When the cap or lid has been opened and the plug removed, the plate can be gripped and lifted up and the catheter therewith drawn out through the portal via the bottom opening.

30

The bottom wall includes on the outside around the transit opening a nipple to which a hose is fitted. The inner diameter of the hose is slightly larger than the outer diameter of the catheter, so as to form a gap seal// therebetween. The gap seal between portal and the patient's body must be sufficiently large to enable the catheters to be readily drawn through the hose both with regard to insertion and withdrawal.

One object of the present invention is to provide a portal arrangement which provides a simple and safe construction for sealing of the outer periphery of the catheter against the bottom wall of the portal.

5 Another object is to design said construction so that it can include a membrane that sealingly screens a sleeve which is connected sealingly to the catheter and which can be pierced by an injection needle for injection of a chosen substance into and through the catheter.

10 A further object is to provide a construction with which the catheter can be removed comfortably and replaced after having been cleaned, or replaced with a fresh catheter.

These objects are achieved either fully or partially by the invention.

15 The invention is defined in the accompanying independent Claim.

Further embodiments of the invention will be apparent from the accompanying dependent Claims.

20 An important feature of the present invention resides in the catheter end portion, which consists of a springy elastic material, such as a plastic material, being pressed sealingly against the bottom wall around its transit opening, while, at the same time, sealing the connecting inner periphery of the catheter around a tubular element inserted into the catheter end portion. This tubular element can be tightened down against the bottom wall
25 of the portal, for instance with the aid of a thread joint, so as to clamp the catheter hose sealingly around its periphery between the tubular element and the edge of the opening through the bottom wall.

30 In one preferred embodiment of the invention, the tubular element has a conical end which is inserted into the catheter hose and which tapers in a direction towards the bottom wall. Moreover, the transit opening in the bottom wall has a conical shape so that the clamping forces will propagate along a longitudinal section of the catheter hose when the conical parts of the sleeve and the transit opening mutually co-act axially.

In one preferred embodiment of the invention, the through-passage channel of the tubular element is screened by a sealing element. This sealing element may have the form of a piercable self-sealing membrane. The membrane can thus be penetrated with a canula of an injection syringe to allow a pharmaceutical preparation to be injected into a patient through the catheter.

The end portion of the tubular element inserted into the end of the catheter may be joined to the catheter by means of a glue joint or some other appropriate joint which will permit the catheter to accompany the tubular element as it is withdrawn from the portal. The catheter and the tubular element will conveniently be fixed to one another upon delivery. As a result of the inventive construction, the transit opening in the bottom wall of the portal will be sealingly screened.

The invention will now be described by way of example and with reference to the accompanying drawing.

Fig. 1 is a schematic axial section view of a portal arrangement according to the invention.

Fig 1 shows a portal whose body 1 is anchored to a layer of tissue 2 (for instance the abdominal wall) in a known manner. The portal body 1 has a generally cupped shape that faces outwards. The portal body also includes a peripherally extending outer anchoring flange 3 that includes openings (not shown) which ensure that the body 1 will be anchored in the tissue 2 particularly securely. Provided in the bottom wall 7 of the portal body 1 is a transit opening 8 for accommodating a catheter hose 9. The opening 8 is shown to narrow conically in an inward direction. The free diameter of the opening 8 is slightly larger than the outer diameter of the catheter 9 so as to allow the catheter to be inserted comfortably through the opening 8. A tubular element 10, i.e. a sleeve, has an external conical end-portion 11 which is received in the end-portion of the catheter 9. The sleeve 10 and the catheter 9 are preferably joined together. The join is conveniently sealingly arranged around the periphery of said end-portion 11 and may have the form of a glue joint, a weld joint, or a joint connection of the kind shown in Fig. 1, where the accommodated end of the catheter clamps elastically against the periphery of the end 11 of the sleeve and one or more sleeve-carried beads 24, preferably disposed around the periphery of the end of said sleeve. The beads 24 may have the form of barbs or flukes that are orientated to make

withdrawal of the catheter from the sleeve 10 difficult to achieve. The conicity of the end of the tubular sleeve 10 corresponds to the conicity of the transit opening 8. The conicity may be in the order of 10° .

5 The illustrated sleeve 10 includes at its outer end a ring flange 16 whose edge lies in close proximity to the inner barrel wall surface of the body 1 so as to centralise the outer end-portion of the sleeve in the body 1. The end-portion 11 of the sleeve 10 is centred in the bottom opening 8 via the catheter hose 11. The inner wall of the body includes at its outer end an internal thread 61. Received in the body 1 is a screw 5 that has an outer thread 62
10 which co-acts with the inner thread 61. The screw 5 includes on its outer part a driver 28, which has the form of a recess in the illustrated case. The screw 5 can be rotated relative to the body 1 with the aid of a tool that has corresponding formations (pins). A washer or plate 38 whose outer diameter corresponds to the inner diameter of the body 1 is placed between the sleeve 10 and the nut 5 ?? The cylindrical washer is conveniently comprised
15 of an elastomeric material, or at least in its central region.

The screw 5 has a central through-passing opening 15 which tapers conically in a direction towards the sleeve 10 and which is preferably filled with and sealingly screened by an elastic body 14.

20 As illustrated, the through-passing channel 12 of the sleeve 10 includes coupling means 17 in the form of an inner thread at its outer part.

Rotation of the screw 5 with the aid of an appropriate tool results in an axial pressure
25 against the sleeve 10, causing the end-portion of the catheter hose 9 to be wedged firmly between the conical end-portion 11 of the sleeve 10 and the corresponding conical wall of the bottom opening 8, so that the inner periphery of the hose 9 will seal against the end-portion 11 of the sleeve and the outer periphery of the hose will seal against the wall of the opening 8. An injection cannula can be inserted through the body 14 and the washer 38 for
30 insertion of a fluid into the catheter hose 9 via the through-passing channel 12 of the sleeve 10. The bodies 14, 38 will preferably be self-sealing in a known manner, when withdrawing the cannula.

The catheter hose 9 can be withdrawn for replacement or for cleaning purposes, by dismantling the screw 5 and the washer 38 and then connecting a tool that has an externally threaded end-portion to the internal thread 17 of the sleeve, whereafter the sleeve 10 can be withdrawn from the body 1 together with the catheter hose 9.

5

The catheter hose 9 may be replaced over a line guide in a known manner, wherein the tool is conveniently designed to provide free passage to the line guide. The person skilled in this art will be aware that the sleeve 10 can be clamped adjustably against the end-portion of the hose 9 with the aid of clamping means other than the screw 8 and the internal thread 61 of the body.

10

The opening 15 of the screw 5 is shown to have a conical shape that narrows in a direction towards the sleeve 10 so as to function as a guide for a cannula as it is inserted through the opening 15 and the washer 38 into the through-passing channel 12. The conicity of the opening 15 may be roughly the same as that shown in the drawing, and has a smallest diameter that corresponds to the free diameter of the through-passing channel 12. The washer 38 may, of course, be joined to the screw 5 and the elastomeric material of said washer may be integral with the elastic body 14 in the through-passing channel 15 of the screw 5.

15

20

The illustrated body 1 has an outer edge bead 41 of enlarged diameter, and a lid or cover (not shown) may be provided for releasably screening the outer end-portion of the body 1.

25

The membrane 14 may be associated or affiliated with the flange 16, and a possible join between sleeve 10 and flange 16 will preferably be made tight by pressing the flange and the sleeve against each other. For example, the flange 16 and the lower part of the sleeve may be separate elements that together establish a tight join that enables the flange 16 and the lower part of the sleeve to be rotated relative to one another. The join may conveniently be rotation-symmetrical relative to the centre axis of the sleeve 10 around which the sleeve rotates generally symmetrically. The join is conveniently formed to hold the upper end of the lower part of the sleeve centred in the portal arrangement.

30

6
CLAIMS

1. A transcutaneous portal arrangement comprising a portal body (1) that includes a recess delimited by a peripheral wall and a bottom wall (7) that includes a through-passing opening (8) which receives a catheter (9), wherein a tubular element (10) has an end-portion (11) which is inserted into the end-portion of the catheter (9), and wherein the portal arrangement includes clamping means (5, 38, 61, 62) for clamping the end-portion of the tubular element (10) against the bottom wall (7) around the through-passing opening (8) such as tightly clamp the outer and the inner wall of the catheter around the edge of the opening (8) and around the periphery of the end-portion (11) of the tubular element respectively, **characterised** in that the clamping means includes a screw (5) which is rotatable relative to the tubular element (10); in that the screw (5) has an external screw thread (62) which co-acts with an internal screw thread on the peripheral wall of the recess; in that the tubular element (10) has a coupling part (17) that can be coupled to a tool for withdrawal of the tubular element (10) from the portal body (1); and in that the tubular element is connected to the catheter for entraining said catheter as the tubular element is withdrawn from the portal body.
2. A portal arrangement according to Claim 1, **characterised** in that the end-portion (11) of the tubular element inserted into the end-portion of the catheter (9) tapers conically in a direction towards the through-passing opening (8); and in that the through-passing opening (8) is conically shaped to correspond to the adjacent conical portion (11) of the tubular element (10).
3. A portal arrangement according to Claim 1 or 2, **characterised** in that the through-passing channel (12) of the tubular element (10) is screened by a sealing element (14, 38) that can be pierced by the cannula of an injection syringe and that is self-sealing subsequent to withdrawal of the cannula.
4. A portal arrangement according to any one of Claims 1-3, **characterised** in that said coupling part includes an internal thread on the inside of the tubular element; and in that the tool includes an external thread that co-acts with said internal thread.

5 5. A portal arrangement according to any one of Claims 1-4, **characterised** in that the sealing element includes an elastomeric washer or insert (38) located between the screw (5) and the tubular element so that in response to compression between said screw and said tubular element the washer will seal against the screw and the tubular element and also
10 against the inner wall of the body (1), wherein the washer (38) can be pierced by a cannula and is preferably self-sealing upon withdrawal of the cannula.

10 6. A portal arrangement according to Claims 4 and 5, **characterised** in that the through-passing opening of the screw tapers conically in a direction towards the tubular element (10).

15 7. A portal arrangement according to any one of Claims 4-6, **characterised** in that the through-passing opening (15) of said screw is screened by a body (14) comprised of a piercable self-sealing material.


20 8. A portal arrangement according to any one of Claims 1-7, **characterised** in that the catheter (9) has an end-portion which is joined to the tubular element (10) by means of a union (24), such as a glue joint, a weld joint, a friction joint, or a barbed joint, so that the catheter hose will be entrained axially by the tubular element upon the withdrawal of said
25 element from said body.

9. A portal arrangement according to any one of Claims 1-8, **characterised** in that the screw (5) is separate from the tubular element.

25 10. A portal arrangement according to any one of Claims 1-9, **characterised** in that at least the catheter end-portion joined to the tubular element consists of an elastomeric material.

1/1

Fig. 1



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/00527

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61M 39/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC-INTERNAL, MEDLINE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9715338 A1 (OSBORNE, THOMAS, A.), 1 May 1997 (01.05.97), figure 1 --	1-10
A	US 4781693 A (FELIX J. MARTINEZ ET AL), 1 November 1988 (01.11.88), figure 1 --	1-10
A	US 5944697 A (JOSEPH E. BICHE), 31 August 1999 (31.08.99), figures 2-3 -- -----	1-10

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

13 June 2003

Date of mailing of the international search report

17-06-2003

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Leif Brander/Els

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/00527

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	9715338	A1	01/05/97	AU	704588 B	29/04/99
				AU	7684496 A	15/05/97
				EP	0868203 A	07/10/98
				JP	11514903 T	21/12/99
US	4781693	A	01/11/88	DE	3477542 D	00/00/00
				EP	0143518 A,B	05/06/85
				SE	0143518 T3	
				ES	535619 A	16/03/86
				ES	8605383 A	01/09/86
				JP	60077766 A	02/05/85
US	5944697	A	31/08/99	NONE		